



VERSA COAT

PREDUSTER/BREADER

Save Money and Create Quick ROI:

- Reduce floor space, changeover time and downtime.
- Decrease breading losses



VersaCoat GENERAL SPECIFICATIONS

	VC 14	VC 24	VC 40	VC 40 HP
Length O/A	2337mm	2337mm	2616mm	2870mm
Width O/A	1092mm	1346mm	1702mm	1702mm
Height O/A	1651mm / 2032mm			1753mm / 2108mm
Infeed Height	All Models - 939mm to 1041mm			
Discharge Height	All Models - 940mm to 1016mm			
Actual Belt Width	406mm	660mm	1016mm	1016mm
Electrical	208-240 VAC 3pH-30AMP / 380-480 VAC 3pH- 20AMP			

ALL MODELS



Specifications are approximate and subject to change

FEATURES

- All settings can be saved in an onboard recipe, simply call up recipe, select, and run
- Hooded for dust control
- Automatic feed system
- No augers
- Built-in blower with variable speed control

Low Breading Charge with Minimal Waste

14" – 23 kilograms flour or 11 kilograms crumb
 24" – 45 kilograms flour or 23 kilograms crumb
 40" – 68 kilograms flour or 34 kilograms crumb



AcuFeeder
 91 kilogram bulk feed hopper

NOTHUM.COM

nothum@nothum.com • +1-417-831-2816 • 631 South Kansas, Springfield, Missouri 65802 USA

Nothum's equipment, concepts and processes may be covered by one or more US and/or international patents. Other US and/or international patents pending.