

COMBOGRILL

MARKING/SEARING



FEATURES:

Various Marking and Searing Options

- Floating marking discs automatically adjust to accommodate irregular products.
- Top and/or Bottom Marking/Searing Options.

MEAT



VEGETABLES



BREAD



ComboGrill GENERAL SPECIFICATIONS

	CG 14	CG 24	CG 40
Length O/A	2083mm	2083mm	2083mm
Width O/A	1092mm	1702mm	1702mm
Height O/A	All Models - 1600mm / 1930mm		
Infeed Height	All Models - 939mm to 1016mm		
Discharge Height	All Models - 939mm to 1016mm		
Actual Belt Width	406mm	660mm	1016mm
Electrical	208-240 VAC 3pH-30AMP / 380-480 VAC 3pH- 20AMP		
Gas	All Models - 1-2 psi / 1" NPT		

Specifications are approximate and subject to change



FEATURES

- 0" – 2" spacing adjustment
- Variable speed belt and marking disc drive
- Propane or Natural Gas.
- Complete gas train assembly enclosed in protected cabinet with automated controls
- Insulated hood and body for safety and product production



NOTHUM.COM

nothum@nothum.com • +1-417-831-2816 • 631 South Kansas, Springfield, Missouri 65802 USA

Nothum's equipment, concepts and processes may be covered by one or more US and/or international patents. Other US and/or international patents pending.