

Specialty Breader

Gain a COMPETITIVE ADVANTAGE

- Designed for coatings with up to 40% moisture

Applies exotic breadings/coatings
to any product



PankoPro

UNIQUE COATING SYSTEM

PankoPro GENERAL SPECIFICATIONS

	PankoPro 24	PankoPro 40
Length O/A	3277mm	3277mm
Width O/A	2286mm	2641mm
Height O/A	All Models - 1651mm / 2007mm	
Infeed Height	All Models - 940mm to 1041mm	
Discharge Height	All Models - 990mm to 1143mm	
Actual Belt Width	660mm	1016mm
Electrical	208-240 VAC 3pH-16.76AMP / 380-480 VAC 3pH- 8.38AMP	

Specifications are approximate and subject to change



FEATURES

- Designed for unique products
- Powered compression rollers and belting, eliminate breakdown of breading/coating/crumbs
- Decrease coating losses
- Very low coating charge with minimal waste
- Breading/Coating versatility



AcuFeeder
91 kilogram bulk
feed hopper

NOTHUM.COM

nothum@nothum.com • +1-417-831-2816 • 631 South Kansas, Springfield, Missouri 65802 USA

Nothum's equipment, concepts and processes may be covered by one or more US and/or international patents. Other US and/or international patents pending.